CHARLES B. GORDON THOMAS P. SCHILLER DAVID B. DEIOMA JOSEPH J. CORSO HOWARD G. SHIMOLA JEFFREY J. SOPKO JOHN P. MURTAUGH JAMES M. MOORE MICHAEL W. GARVEY RICHARD A. SHARPE RONALD M. KACHMARIK PAUL A. SERBINOWSKI BRIAN G. BEMBENICK AARON A. FISHMAN

PATENT, TRADEMARK, COPYRIGHT AND RELATED INTELLECTUAL PROPERTY LAW

REARNE & GORDON LLP

ATTORNEYS AT LAW

1801 EAST 9TH STREET **SUITE 1200**

CLEVELAND, OHIO 44114-3108

(216) 579-1700 FAX: +1 (216) 579-6073

EMAIL: ip@pearnegordon.com

STEPHEN S. WENTSLER ROBERT F. BODI SUZANNE B. GAGNON DEBORAH L. CORPUS RAYMOND N. RUSSELL, PH.D. UNA L. LAURICIA STEVEN J. SOLOMON GREGORY D. FERNENGEL BRAD C. SPENCER, P.E. BRYAN M. GALLO OF COUNSEL LOWELL L. HEINKE THADDEUS A. ZALENSKI PATENT AGENTS
TOMOKO ISHIHARA

CHRISTOPHER P. DEMAS

J. GREGORY CHRISMAN

October 20, 2006

Mail Stop Certificate of Corrections Branch Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Re:

U.S. Patent No.: 7,031,480

Issued: April 18, 2006

Inventor: Tooru Himori et al.

Our Docket: 34158

Certificate

OCT 2 7 2006

of Correction

Sir:

A Certificate of Correction under 35 U.S.C. 254 is hereby requested to correct Patent Office printing errors in the above-identified patent. Enclosed herewith is a proposed Certificate of Correction (Form No. PTO-1050) for consideration along with appropriate documentation supporting the request for correction.

It is requested that the Certificate of Correction be completed and mailed at an early date to the undersigned attorney of record. The proposed corrections are obvious ones and do not in any way change the sense of the application.

We understand that a check is not required since the errors were on the part of the Patent and Trademark Office in printing the patent.

Very Huly yours,

Michael W. Garvey, Reg. No. 35878

OCT 3 0 2006

MWG:aez **Enclosures**

> I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Mail Stop Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date indicated below.

Michael W. Garvey

Name of Attorney for Applicant(s)

Signature of Attorney

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

7,031,480

PAGE 1 OF 1

DATED

April 18, 2006

INVENTOR(S)

Tooru Himori and Yoshinobu Yasuno

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 16, Column 19, Line 6, please delete "easing", and insert therefor -casing-.

Claim 16, Column 19, Line 7, please delete "easing", and insert therefor -casing-.

MAILING ADDRESS OF SENDER:

Michael W. Garvey Pearne & Gordon LLP 1801 East 9th Street **Suite 1200**

Cleveland, Ohio 44114-3108

PATENT NO. 34158

No. of additional copies

0

OT PE 403

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appln. No.

09/993,416

Confirmation No.:

6837

Applicant

Tooru Himori, et al.

Filed

November 16, 2001

TC/A.U.

2646

Examiner

Dionne Harvey

Docket No.

34158

Customer No.

000116

Mail Stop Amendment Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

AMENDMENT

Sir:

In response to the Office action of August 10, 2005, please amend the above-identified application as follows:

Amendments to the Claims are reflected in the listing of claims which begins on page 2 of this paper.

Amendments to the Abstract begin on page 8 of this paper.

Remarks begin on page 9 of this paper.

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Mail Stop Amendment, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date indicated below.

James M. Moore

Name of Attorney for Applicant(s)

Date

Signature of Attorney

Appl. No. 09/993.416 Amdt. Dated November 10, 2005 Reply to Office action of August 10, 2005

a cylindrical casing space;

an electrode plate accommodated in said casing space of said casing member; an electrically insulating member in the form of an annular ring shape and

accommodated in the casing space of the casing member to be held in coaxial alignment

with the casing member;

a plurality of electrically connecting members each intervening between said printed circuit board and said electrode plate to have said printed circuit board and said electrode plate electrically connected with each other, said electrically connecting members being partly retained by said electrically insulating member and disposed on and along the circumference of said printed circuit board to be equidistantly spaced apart from one another; and

a diaphragm located between said inlet portion of said casing member and said electrode plate to be spaced apart along said center axis of said casing member from said electrode plate at a predetermined space distance.

Claim 15 (currently amended) An electret condenser microphone as set forth in claim 14, in which further comprises an said electrically insulating member accommodated is in said casing space of said casing member and provided on said printed circuit board, in which said electrode plate is mounted on said electrically insulating member and retained by said electrically insulating member.

Claim 16 (original) An electret condenser microphone as set forth in claim 14, which further comprises a diaphragm supporting member accommodated in said casing space of said casing member and supported by said inlet portion of said casing member, in which said diaphragm is mounted on said diaphragm supporting member and supported by said diaphragm supporting member.

Claim 17 (original) An electret condenser microphone as set forth in claim 14, which further comprises an electrically insulating spacer intervening between said electrode plate and said diaphragm to have said electrode plate and said diaphragm spaced apart from each other at said predetermined space distance.

Claim 18 (original) An electret condenser microphone as set forth in claim 14, which further comprises a covering member provided on said inlet portion of said casing member.